

ARECA

Pink antifreeze

Organic antifreeze based on ethylene glycol, phosphate, nitrite, amine and borax free.

It offers excellent protection against freezing and against oxidation and corrosion of metals. Its composition of organic inhibitors not consumed in service will guarantee longevity of the fluid and therefore of the engine.

Antifreeze adapted to Volkswagen vehicles.

Product to be diluted (see dilution table), do not use pure. Always refer to manufacturer's recommendations before using the product.

Specifications

This antifreeze can be used when the following level of performance is needed:

- ✓ VW/Audi/Seat/Skoda TL-774-D/F (G12/G12+)
- ✓ MB 325.3

Physicochemical Characteristics

Characteristics	Method	Units	Typical value	Min.	Max.
Aspect	Visual	-	Limpid homogenous		
Colour	Visual	-	Pink		
Odour	Olfactory	-	Characteristic		
Density	D 20/4	-	1.119	-	-
Flash point	NF M 07 011	°C	137	110	-
Freezing point @ 50%*	ASTM D 1177	°C	-37.5	-	-37.0
pH @ 50%*	NF T 78 103	pH	8.1	7.5	8.5
Alcalinity reserve à 50%*	NF T 78 101	ml HCL 0.1N	7.4	6.0	-
Boiling point	NF R 15 602-1	°C	172	160	-
Glassware corrosion	NF R 15 602-7	mg/sample			
Copper			-0.7	-5.0	+5.0
Aluminium AW			-0.1	-10.0	+10.0
Brass			0.0	-5.0	+5.0
Steel			-0.6	-2.5	+2.5
Cast Iron			0.2	-4.0	+4.0
Aluminium			0.3	-10.0	+10.0
Hot plate corrosion	NF R 15 602-8	mg/cm ² /week	-0.5	-1.0	+1.0

* Volume

Dilution table

Antifreeze (% Vol.)	Demineralized water (% Vol.)	Freezing point (°C)
50	50	-37
40	60	-24
33	67	-17

Do not dilute below 33% in order to maintain anti-corrosion properties of the product.

Security

See Safety Data Sheet

This product contains a repellent agent in accordance with French Decree No. 95-326 of March 20th, 1995