ARECA 75W-80

Mechanical transmission fluid 75W-80 GL-5

Fluid for mechanical transmission.

Its "extreme pressure" and anti-wear properties provide good protection for mechanical transmissions requiring a lubricant meeting GL-5 performance level and 75W-80 viscosity grade.

Always refer to the manufacturer's recommendations before using the product.

Specifications

- ✓ API GL-5
- ✓ MIL-L-2105D
- ✓ ZF-TE-ML 08, 17B
- ✓ Volvo 1273.10

Physicochemical Characteristics

Characteristics	Method	Unit	Typical value	Min.	Max.
Viscosity grade	SAE J306	-	75W-80	-	-
Kinematic viscosity @ 100°C	ASTM D 7042	cSt	9.8	9.7	10.5
Kinematic viscosity @ 40°C	ASTM D 7042	cSt	58	-	-
Viscosity index	ASTM D 2270	-	157	-	-
Density @ 20°C	ASTM D 7042	-	0.857	-	-
Pour point	ASTM D 97	°C	-43	-	-
Flash point	ASTM D 92	°C	232	-	-
Brookfield viscosity @ -40°C	ASTM D 2896	cP	139000	-	150000
Spectrometric analysis Phosphorus Sulfur	ICP	ppm	 380 19400	 - -	 - -
Colour	Visual	-	Blue green / Green		

Security

See Safety Data Sheet