ARECAFLUID 100

UTTO

Universal transmission fluid for construction machinery and agricultural equipment with a common transmission casing including wet brakes.

Specifications

- ✓ John Deere J20C / D
- ✓ Massey Ferguson CMS 1135 – 1143 – 1145
- ✓ Ford ESN-M2C-86C – ESN-M2C-134D
- ✓ Allison C4
- ✓ CASE MS1207, 1209
- ✓ CNH MAT 3525 (FNHA-201.00= M2C 134D) – MAT 3526 (FNHA 2-C-200.00)
- ✓ API GL4+
- ✓ Caterpillar TO-2
- ✓ ZF TE-ML 06B, 06R

Physicochemical Characteristics

Caracteristics	Method	Units	Typical value	Mini	Maxi
Viscosity grade	SAE-J	-	10W30	-	-
Kinematic viscosity @ 100°C	ASTM D 7279	cSt	11.1	9.6	12.2
Kinematic viscosity @ 40°C	ASTM D 7279	cSt	62.0	-	-
Density	D 20/4	-	0.865	-	-
Brookfield viscosity @ -18°C	-	cP	3500	-	4000
Brookfield viscosity @ -35°C	-	cP	63900	-	70000
T.B.N.	ASTM D 2896	mg KOH/g	10.6	9.6	11.6
Colour	ASTM D1500	-	4.0	-	5.0

Security

See Safety Data Sheet