

ARECA S3200**Semi-synthetic engine oil 10W40**

Semi-synthetic passenger car engine oil adapted to petrol, Diesel, high pressure direct injection Diesel.

Specifications

- ✓ ACEA A3 / B4
- ✓ API SN / CF
- ✓ VW 502.00 / 505.00
- ✓ MB 229.3
- ✓ Renault RN 0700 / RN0710
- ✓ PSA B71 2300
- ✓ JASO MA2

Physicochemical Characteristics

Characteristics	Method	Units	Typical value	Mini	Maxi
Viscosity grade	SAE-J	-	10W40	-	-
Kinematic viscosity @ 100°C	ASTM D 7279	cSt	14.5	14.0	16.3
Kinematic viscosity @ 40°C	ASTM D 7279	cSt	98	-	-
Viscosity index	ASTM D 2270	-	145	-	-
CCS viscosity @ -25°C	ASTM D 5293	mPa.s	6600	-	7000
HTHS viscosity @ 150°C	CEC-L-36-A-97	mPa.s	3.9	3.5	-
MRV viscosity @ -30°C	ASTM D4684	mPa.s	-	-	60000
Density	D 20/4	-	0.862	-	-
Pour point	ASTM D 5950	°C	-39	-	-
T.B.N.	ASTM D 2896	Mg KOH/g	10.2	10.0	11.5
Sulfated ash	ISO/FDIS 3987	% mass	1.16	1.0	1.5
Spectrometric analysis	ICP	ppm			
Phosphorus			1000	910	1100
Zinc			1100	1000	1200
Calcium			3100	2800	3380
Magnesium			-		
NOACK volatility	ASTM D 5800	% mass	9	-	12
Color	ASTM D1500	-	4.0	-	4.5

Security

See Safety Data Sheet