

**ARECA 3D SAE 10W****Monograde oil SAE 10W**

Monograde oil SAE 10W for various uses:

- Fixed fluid or industrial engines
- Non-extreme pressure transmissions
- Detergent and anti-wear hydraulic oil

**Specifications**

- ✓ API CG-4
- ✓ API SJ / CF / CF-4
- ✓ Allison C4

**Physicochemical Characteristics**

Characteristics	Method	Units	Typical value	Mini	Maxi
Viscosity grade	SAE-J	-	10W	-	-
Kinematic viscosity @ 100°C	ASTM D 7279	cSt	5.8	4.8	7.5
Kinematic viscosity @ 40°C	ASTM D 7279	cSt	36	-	-
Viscosity index	ASTM D 2270	-	100	90	-
CCS viscosity @ -25°C	ASTM D 5293	mPa.s	-	-	7000
MRV viscosity @ -30°C	ASTM D4684	mPa.s	-	-	60000
Density	D 20/4	-	0.863	-	-
Pour point	ASTM D 5950	°C	-36	-	-
T.B.N.	ASTM D 2896	Mg KOH/g	8.5	7.8	9.3
Spectrometric analysis Phosphorus Zinc Calcium Boron	ICP	ppm	760 830 2760 70	± 10 %	
Color	ASTM D1500	-	4.0	-	4.5

**Security**

See Safety Data Sheet