

ARECA TRANSMATIC VI**Automatic transmission fluid ATF VI**

Top of the range fully synthetic automatic transmission fluid (hydrokinetic) with very specific viscosity to meet Dexron® VI requirements.

Specifications

Meets Dexron® VI requirements.

See details of Original Equipment Manufacturers covered in back spreadsheet.

Physicochemical Characteristics

Characteristics	Method	Units	Typical value	Mini	Maxi
Kinematic viscosity @ 100°C	ASTM D 7279	cSt	5.9	5.7	6.1
Kinematic viscosity @ 40°C	ASTM D 7279	cSt	28.6	-	-
Viscosity index	ASTM D 2270	-	158	150	-
Pour point	ASTM D 5950	°C	-	-	-50
Density	D 20/4	-	0.837	-	-
Brookfield viscosity @ -40°C	ASTM D 2983	cP	8300	-	11000
Color	Visual	-	Red	-	-

Security

See Safety Data Sheet

Manufacturers	Applications
ATF	Shell 3353
	Shell 134
	Shell M-1375.4/M-1375.6/M-1375.8
Bentley	P/N PY112995PA
BMW / Mini	P/N 83 22 0 142 516
	P/N 83 22 0 397 114/163 514
	P/N 83 22 2 152 426
Chrysler / Dodge / Jeep	P/N 05127382AA
	P/N 68043742AA
	P/N 68157995AA
Ford / Lincoln / Mercury	P/N XT-10-QLV [LV]
	P/N XT-6-QSP or -DSP [SP]
GM / GMC Opel / Saturn	AW1
	Dexron VI
	P/N 88863400
	P/N 88863401
Honda / Acura	DW-1
Hyundai / Kia	NWS-9638 T-5
	P/N 040000C90SG
	SP-IV/SPH-IV
Jaguar	Fluid 8432
JASO	M315, Class 1A
Land Rover	P/N TYK500050
	P/N LR0022460
Maserati	P/N 231603
Mazda	FZ
Mercedes / Daimler	MB 236.12/14/15/41
Mitsubishi	ATF-J3
Nissan / Infinity	Matic-S
Porsche	P/N 000 043 304 00
Saab	P/N 93 165 147 - AW-1
Toyota / Lexus / Scion	Type WS
Volkswagen / Audi	G 052 533
	G 055 005 (-A, -A2)
	G 055 540 (A2)
	G 055 162 (-A2, -A6)
	G 060162 (-A1, -A2, -A6)